Description

SUPERTUB+ Laundry Tub 348mm with ALL PRESSURE Gooseneck tap

STSLIMTAPAP











Dimensions





Dated 01/11/2026

Specifications

Tapware	
Tapware type	#304 Stainless Steel Tap – **LEAD FREE**
WELS rating	5 Stars, 5.5L per minute (Mains Pressure) 3 Stars, 8.5L per minute (low pressure)
Max & Min pressure	Maximum pressure 72.5 PSI (500 kPa); Minimum pressure 22 PSI (150 kPa)
Temperature range	Recommended temperature range 5° to 65°C; Maximum temperature 80°C
Sink	
Bowl type	0.8mm polished #304 Stainless Steel
Bowl capacity	20L gross capacity measured to the top; 16L capacity to overflow
Waste type/ discharge flow rate	Plug waste/ 60L per minute
Overflow/ Flow rate	Yes/ 30L per minute
Cabinet	
Handle type	Recessed plastic handle
Door opening	Reversible, can be either left- or right-hand opening
Adjustable levelling feet	Yes
Side apertures for hoses	Yes, on both sides
3 Way ball valves isolators	Yes, included
Washing machine waste pipe	Separate
Cabinet colour/finish	Satin white powder coated
Cabinet material	0.6mm galvanized steel
Maximum height of items can be stored	510mm
Dimensions & Weights	
Product dimensions (mm)	W348*D564*H902-922
Carton dimensions (mm)	W368*D585*H965
Gross/Net weight (Kg)	17/14
Warranty	
Tapware & Cabinet	2 years on parts & labour from the date of purchase
Sink	5 years on parts & labour from the date of purchase