

Procoat Premium Exterior Timber Oil

The ultimate product for exterior timber - rejuvenate, protect and enhance your exterior timber with this ultra-premium penetrating oil.

An ultra-premium, fast drying and penetrating oil designed specifically for exterior timber. The unique formulation is enriched with tung oil to nourish, rejuvenate and protect the timber, and the natural colour pigments enhance the timber grain.

Product Procoat Premium Exterior Timber Oil PR409

Typical Uses May be used on suitably prepared:

- Timber decking including pine, kwila and vitex
- Exterior timber furniture
- Timber cladding
- Smooth or rough sawn exterior timber, beams, pergolas
- All other exterior timber

Physical Properties

Binder type	Modified alkyd / tung oil blend
Solvent	White spirits
Colour	Range of standard colours
Dry time	4 hours at 20°C
Recoat time	16 hours at 20°C
Number of coats	1 – 2
Theoretical coverage	Up to 12m ² per litre, depending on timber
Thinning and clean up	Mineral turps or white spirits

Preparation Ensure the surface is in sound condition, dry, and free from dirt, dust and other contaminants. Oils and grease must be removed with a suitable cleaner. Where there has been mould, treat the area with a moss and mould remover. Treat old weathered timber with Procoat Timber Cleaner and Brightener to remove dead wood fibres and discolouration.

Stir well during use and during use with a broad flat paddle, using an up and down scooping motion.

If multiple tins of stain are being used, we recommend mixing them all together to ensure a consistent colour.

Do not apply to new dressed timber or timber that is damp. Allow timber to fully dry and weather before staining. LOSP pine should be weathered for 2 weeks to improve uptake, and dense timbers like kwila should be weathered for 4-6 weeks to ensure adequate resin bleed has occurred.

Any timber showing signs of mill glaze should be sanded to improve penetration.

Application Procoat Premium Exterior Timber Oil may be applied by brush or applicator pad. Consult your local paint specialist for recommendations.



Bare timber

1. Apply 1 coat of Procoat Premium Exterior Timber Oil, ensuring it is worked well into the timber
2. A second coat may be required on rough sawn timbers

Previously stained surfaces

1. Wash well with Procoat Deck and Exterior House Wash and treat as above
2. Apply 1 coat of Procoat Premium Exterior Timber Oil, ensuring it is worked well into the timber

Note: Excessive coats will cause a varnished look and may lead to early failure of the stain. When re-oiling, always check the absorbency of the substrate, if the oil doesn't penetrate, sand back to bare timber.

Maintenance

All new work should have a second application of oil applied after the first summer to allow the timber and oil to weather in.

Performance and Limitations**Performance**

- Enriched with tung oil to nourish, rejuvenate and protect exterior timber
- Enhances the natural beauty of the timbers grain
- Perfect for decks and timber furniture, and most other exterior timber
- Protects against mould and algae growth
- Made specifically in NZ for NZ conditions

Limitations

- Not to be used over any surface that has been previously painted
- Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period
- Stop staining 4 hours before dew fall, or if rain looks likely
- Stain may darken or change colour progressively as timber weathers

Health and Safety

For detailed health and safety information refer to Material Safety Datasheet (MSDS)

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

The logo for Procoat, featuring the word "procoat" in a bold, lowercase, sans-serif font. A horizontal line is positioned above the "o" and "c", extending from the "p" to the "t".

Disclaimer

Copyright Aalto Group Ltd. 2024

Any information provided in this data sheet is provided in good faith and is correct at the time of publication. Application details are based on generic scenarios, for any specific application details please contact your Aalto paint specialist.

Products and coating systems can be expected to perform as stated in this data sheet, provided the substrate is in good condition, preparation is completed to a high standard, and application is carried out by a suitably experienced/skilled applicator.

The logo for Procoat, featuring the word "procoat" in a bold, lowercase, sans-serif font. A horizontal line is positioned above the "o" and "c", extending from the "p" to the "t".