

net contents 1 litre

A-LL370101 6/13

WARNING

Read label before use. Keep out of reach of children. Causes skin irritation. Causes eye irritation. May damage fertility or the unborn child. Suspected of damaging organs through prolonged or repeated inhalation. May cause respiratory irritation.

ALUMINIUM: May cause an allergic skin irritation. Suspected of causing cancer.

PRECAUTIONS

Ensure all safety directions are read and understood before handling. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

ALUMINIUM: Do not allow contaminated clothing out of the workplace.

FIRST AID

IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing and wash before re-use. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

INHALATION: Remove to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

If exposed or concerned, seek medical advice.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST. POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

CONTAINS: White: Liquid Hydrocarbons 27-29%, Methyl Ethyl Ketoxime <0.1%. Aluminium: Liquid Hydrocarbons 35-39%, Methyl Ethyl Ketoxime <0.2%.

For use as a surface preparation coating.

For full technical instructions see Data Sheet D40 (white); D46 (aluminium).

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, carbon dioxide or dry chemical powder.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Wood Primer
general purpose
solventborne exterior/interior



WHITE

Resene Wood Primer is based on an oil-modified alkyd resin blended with pigments to give ease of application and good penetration to substrates. Flexible and produces the ideal surface for subsequent paint finishes.

Preparation

- Ensure surfaces to be painted are in sound condition, thoroughly sanded, dry, free from dirt, dust and loose material, oil and grease.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Fill cracks and holes with an appropriate filler after priming.
- Round all sharp timber edges. Any bare timber surface that has been left exposed to the weather for more than one week must be thoroughly sanded or treated with Resene TimberLock (see Data Sheet D48).

All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

- Resene Quick Dry (see Data Sheet D45) must be used as the first coat on Matai, Spotted Gum and Totara.
- Resene Aluminium Wood Primer is useful if a high standard of surface preparation cannot be achieved, if knots exist or if staining is a problem.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or Reseller.

Application

- Pretreatment with Resene TimberLock is recommended on Cedar and weathered timber surfaces.
- Apply one full coat. Allow 24 hours to dry before topcoating. Resene Wood Primer is best applied by brush to ensure full surface wetting is achieved.
- Where possible prime all timber faces with particular attention to end grains, nailheads, splits, corners and joints.

Overcoating

- Resene Wood Primer requires a minimum of two full topcoats to be applied.

• Resene Wood Primer should not be exposed to the weather for long periods. Consult your Resene ColorShop if recoating after one month.

- For best results Resene Enamel Undercoat (see Data Sheet D44) should be applied over Resene Aluminium Wood Primer.
- Under certain conditions waterborne paints may crawl or ciss over Resene Wood Primer. Wiping with clean turps or a dilute detergent solution will rectify the condition.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 – PAINT RELATED MATERIAL



In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Exterior and interior woodwork (except Matai, Spotted Gum and Totara).

Gloss level: Low sheen (white) and metallic silver (aluminium).

Coverage: 12 square metres per litre per coat.

Dry time (minimum): 6 hours (white) and 24 hours (aluminium).

Recoat time (minimum): 24 hours. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Usual number of coats: One.

Application method: Brush or roller.

Thinning and clean up: Mineral turps.

Colour range: White or aluminium.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.